

(12) United States Patent

Vangura

US 9,409,813 B2 (10) **Patent No.:**

(45) **Date of Patent:** Aug. 9, 2016

(54) HAND-HELD TOOL FOR CUTTING LAMINATED GLASS AND FILM-COVERED GLASS AND METHOD FOR USING SAME

(71) Applicant: Albert Vangura, Gibsonia, PA (US)

Inventor: Albert Vangura, Gibsonia, PA (US)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35 U.S.C. 154(b) by 458 days.

Appl. No.: 13/657,741

(22)Filed: Oct. 22, 2012

Prior Publication Data (65)

US 2013/0283985 A1 Oct. 31, 2013

Related U.S. Application Data

(60) Provisional application No. 61/549,345, filed on Oct. 20, 2011.

(51)	Int. Cl.	
	B26B 15/00	(2006.01)
	C03B 33/07	(2006.01)
	C03B 33/12	(2006.01)
	B26D 1/30	(2006.01)
	B26D 1/00	(2006.01)

(52) U.S. Cl.

CPC C03B 33/076 (2013.01); B26B 15/00 (2013.01); B26D 1/30 (2013.01); C03B 33/07 (2013.01); C03B 33/074 (2013.01); C03B 33/12 (2013.01); B26D 2001/006 (2013.01); B26D 2001/0066 (2013.01); Y10T 83/04 (2015.04)

(58) Field of Classification Search

CPC C03B 33/076; C03B 33/074; C03B 33/12; C03B 33/07; B26B 15/00; B26D 2001/006; B26D 2001/0066; Y10T 83/04

See application file for complete search history.

(56)**References Cited**

U.S. PATENT DOCUMENTS

A	5/1960	Docken
A	5/1974	Sumida
A	11/1979	Sidenstick et al.
A	10/1996	Eisenbraun
A *	6/1998	Rusch et al 156/108
A	11/1999	Rogers
Α		Fladgard et al.
\mathbf{S}	6/2001	Fladgard et al.
B2	12/2009	Fladgard et al.
$\mathbf{A}1$	2/2003	Fladgard et al.
A1	3/2004	Renecker et al.
A1	9/2006	Edwards et al.
	A A A A A S B2 A1 A1	A 5/1974 A 11/1979 A 10/1996 A * 6/1998 A 11/1999 A 11/1999 S 6/2001 B2 12/2009 A1 2/2003 A1 3/2004

FOREIGN PATENT DOCUMENTS

EP	2177482	4/2010
WO	2006104523	5/2006

^{*} cited by examiner

Primary Examiner — Omar Flores Sanchez (74) Attorney, Agent, or Firm — Blynn L. Shideler; Krisanne Shideler; BLK Law Group

ABSTRACT (57)

An apparatus for cutting laminated glass and film-covered glass includes a powered hand-held tool with a blade set including two static cutting blades and one dynamic, reciprocating cutting blade. The reciprocating cutting blade moves between the two static cutting blades which are rigidly mounted to the tool head. The left and right static cutting blades were spaced apart by about 0.250 inches, and the cutting blade had a thickness of about 0.200-0.250 inches. The clearance between the reciprocating and each static blade is between about 0.005-0.025 inches.

10 Claims, 2 Drawing Sheets

